

Ecoline

The easy entry into automated pastry production.



The Ecoline is a compact make-up line which allows you to begin automated production for folded and rolled pastry products. Designed and manufactured in our factory in Switzerland, it unites all the qualities that characterise ROND0 machines at a low price.

The benefits at a glance

Compact design

- Two different lengths
- Length with dough band positioner: 4.2 m / 6.2 m
- Length with calibrator: 5.4 m / 7.4 m

High process reliability

- Twin cutting station with counter-pressure rollers
- Precise belt drive at product discharge
- Consistent cutting length through intelligent drive concept

Simple operation

- Touch panel interface for controlling the line, the guillotine and two driven accessories
- 99 storable programs

High flexibility

- A wide variety of accessories for many different types of products
- Unique decorating cutting rollers for customising products
- Moveable Guillotine for high flexibility

High reliability

- Swiss-made
- Worldwide ROND0 Service
- Meets international safety standards

Standard equipment

- Twin cutting station with counter-pressure rollers
- Movable guillotine with knife and hold-down device
- Quick-release belt
- Touch panel
- Dough band positioner
- Holder for cutting rollers
- Bottom plate

Starter Kit Accessory

- Length cutting shaft with six knives
- Gauge for setting the cutting blades
- Holder for folding shoes
- Folding shoes for 4-row production of
 - Single-fold products
 - Double-fold products with seal on top
 - Double-fold products with seal on bottom

Options

- Ecoline Calibrator
- Accessories

Filling depositors

- Mechanical filling depositor for 4- or 6-row production
- Fix installed pneumatic filling depositor for 4- or 6-row production
- Moveable pneumatic filling depositor for 4- or 6-row production

Technical data

Ecoline	SEL401	SEL601
Total length	4.0 m	6.0 m
Length with dough band positioner	4.2 m	6.2 m
Length with Ecoline Calibrator	5.4 m	7.2 m
Table width	715 mm	
Table height	915 mm	
Working width	600 mm	
Belt speed	0.5 – 8 m/min	
Running direction	right - left	
Drive	on outfeed side	
Supply voltage	3 × 200 – 480 V, 50/60 Hz	
Control voltage	24 V DC	
Operation	<ul style="list-style-type: none"> • Microprocessor control system • Touch panel • 99 program memory slots 	
Max. number of driven accessories	2	
Interfaces	to the calibrator	

The right to make changes of a technical nature is reserved. The technical safety and type-specific instructions in the operating manual must be complied with. Prohibition, information and warning signs on the machines are to be complied with in accordance with the operating manual.



RONDO Burgdorf AG
3400 Burgdorf / Switzerland
Tel. +41 34 420 81 11
info@rondo-online.com

RONDO Schio s.r.l.
36015 Schio (VI) / Italy
Tel. +39 0445 575 429
info.it@rondo-online.com

RONDO GmbH & Co. KG
57299 Burbach / Germany
Tel. +49 2736 203-0
info.de@rondo-online.com

RONDO S.à.r.l.
67319 Wasselonne Cédex / France
Tel. +33 3 88 59 11 88
info.fr@rondo-online.com

RONDO Ltd.
Chessington, Surrey KT9 1ST / UK
Tel. +44 20 8391 1377
info.uk@rondo-online.com

000 RONDO Rus
127495 Moscow / Russia
Tel. +7 495 419 51 23
info.ru@rondo-online.com

RONDO Inc.
Moonachie, N.J. 07074 / USA
Tel. +1 201 229 97 00
info.us@rondo-online.com

RONDO Asia Sdn. Bhd.
58200 Kuala Lumpur / Malaysia
Tel. +60 3 7984 55 20
info.my@rondo-online.com

RONDO China
Regional Office
Guangzhou 510700 / China
Tel. +86 20 8388 2211
info.cn@rondo-online.com

RONDO México
Regional Office
C.P. 15530 México, D.F. / Mexico
Tel. +52 55 2580 7075
info.mx@rondo-online.com

www.rondo-online.com